

EP9

Tiles Bonding Agent



Easy Apply



Excellent Bonding



**Solution to
Tile Popping**

20L / 5L



EP9 is a special formulated homopolymer bonding agent for the latest construction needs like tiles overlay and tiling without back screed. It has special plasticiser agent added to improve bonding strength for various substrates and suitable for all cementitious products.

WHERE TO USE

- Concrete top up.
- Window coping installation.
- Designed for indoor application.
- Metal door and window frames.
- Pebble wash to any solid substrate.
- New and old cement plastered surfaces.
- Tile on tile, marble on marble or granite on granite.
- Cemboard, wood, metal, ceramic/porcelain tiles, concrete substrate, brick and marble surfaces.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

The surface must be structurally sound and clean, free of oil, grease, wax, dust sand, dirt, laitance, paints, efflorescence, curing compounds, loose materials of any type. If the surface is questionable, apply a small test patch of **EP9**. Allow to completely dry and observe for any sign of lifting, wrinkling, peeling or curling. If these occurred, additional surface preparation is recommended. Recommending cleaning methods by washing or high-pressure water jets.

- **EP9** can be applied with paint roller or paint brush.
- Open the original packing and use as it is, do not dilute with water or solvent. Do not add any admixture.
- Never shake and box mixed as to entrap air bubble.
- Approximately 30 minutes of drying time, subsequent activities can be carried out (eg plastering or tiling). Subsequent application of plastering, skim coating and cement mortar for tiling shall be performed within 14 days provided **EP9** is clean, dust free, uncontaminated and intact.
- Do not use water soluble materials such as glue, calcimine, wallpaper, casein-based adhesive or where constant moisture is present.
- Do not apply to frozen or frost covered surface or temperature is below 50°F (10°C).
- Do not apply to wet surface where there may be hydrostatic pressure such as retaining walls and swimming pool.

Product Information	Packaging: 20L / 5L
Colour	Green
Shelf Life	12 months
Open Time	14 days
Drying Time	Approximately 30 minutes after applied, depending on the temperature and humidity (18°C - 45°C)
Toxicity	Non-toxic
Fire Hazard	Non-flammable
Application Method	Can be applied with paint roller or paint brush
Coverage	Approximately 18 - 20m ² /litre depending on the method of application, temperature, porosity and texture of the substrate/surface
Storage Conditions	Proper storage in original unopened and undamaged sealed packaging in dry conditions at temperature between +10°C and +37°C. Keep away from direct sunlight, rain and water
Clean Up	Cleaning may be accomplished with water immediately after use

KEEP OUT OF REACH OF CHILDREN

Disclaimer: The information presented is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, incurred in connection with the use of these product, date or suggestions.

CAUTIONS

Do not take internally. Avoid contact with skin and eyes. In case of skin contact, wash affected area with soap and water. In case of eye contact, flush with water for 15 minutes and get prompt medical attention.

